

SAFETY DATA SHEET

Product Name: Epic Bond Promoter

SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION

Manufacturer/Distributor Name: Ultra Durable Technologies, Inc.
1415 5th St N
St. Cloud, MN 56303
800-722-2998 – www.ultraDT.com

24 Hour Emergency Phone Numbers: CHEMTREC within the United States 1-800-424-9300
CHEMTREC within Canada +1 703-527-3887

SECTION 2 – HAZARDS IDENTIFICATION

Classifications:

Health: Category 2
Flammability: Category 4
Reactivity: Category 5

Signal Words:

Danger

Hazard Statements:

H318: Causes serious eye damage.
H402: Harmful to aquatic life.

Precautionary statements:

Prevention:

P273: Avoid release to the environment.
P280: Wear eye protection/face protection.

Response:

P305+P351+P338+P310: If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

Storage:

P404: Store in a closed container.

Disposal:

P501: Dispose of contents/container to an approved waste disposal plant.

Hazard Pictogram:



SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS

Composition / Information on ingredients mixtures:

Glycidoxypropyltrimethoxysilane, minimum purity 98%
Methanol 67-56-1 <0.2

Minor Impurities: Not determined

CAS Number: 2530-83-8

EINECS Number: 219-784-2

RTECS Number: VV4025000

SECTION 4 – FIRST AID MEASURES

Eye: Immediately flush with water for 15 minutes.

Skin: Remove from skin and wash thoroughly with soap and water or water less cleanser. Get medical attention if irritation or other ill effects develop or persist.

Inhalation: Remove to fresh air. Get medical attention if ill effects persist.

Oral: Get medical attention. Do not induce vomiting.

Comments: Treat symptomatically and supportively.

SECTION 5 – FIREFIGHTING MEASURES

General Information: As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. Water reactive. Material will react with water and may release a flammable and/or toxic gas.

Flash Point: 122 deg C (251.60 deg F)

Auto ignition Temperature: 400 deg C (752.00 deg F)

Extinguishing Media: Use foam, dry chemical, or carbon dioxide. DO NOT USE WATER!

Explosion Limits, Lower: Not available.

Upper: Not available.

NFPA Rating: (estimated) Health: 2; Flammability: 1; Instability: 2; Special Hazard: -W-

SECTION 6 – ENVIRONMENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

6.3 Methods and materials for containment and cleaning up

Soak up with inert absorbent material and dispose of as hazardous waste. Keep in suitable, closed containers for disposal. Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Do not breathe mist or vapor. Ensure adequate ventilation. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. In case of spills, beware of slippery floors and surfaces. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. See Section 8 of the SDS for Personal Protective Equipment.

SECTION 7 – HANDLING AND STORAGE

Handling: Do not get in eyes, on skin, or on clothing. Do not ingest or inhale. Use with adequate ventilation. Do not allow contact with water. The product is immiscible with water and will sediment in water systems.

Storage: Store in a cool, dry place. well-ventilated place. Protect from moisture. Keep from freezing. Prevent including any incompatibilities contact with water or air and store in air-tight containers in vacuum or in inert atmosphere. Never leave unsealed.

SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls:

Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Use adequate ventilation to keep airborne concentrations low.

OSHA Vacated PELs: 3-Glycidoxypropyltrimethoxysilane: No OSHA Vacated PELs are listed for this chemical.

Exposure Limits:

Chemical Name	ACGIH	NIOSH	OSHA – Final PELs
Methanol (CAS 67-56-1)	STEL 250 ppm TWA 200 ppm	STEL 325 mg/m3 250 ppm TWA 260 mg/m3 200 ppm	Table Z-1 limits (29 CFR 1910.1000)

Personal Protective Equipment For Routine Handling:

Eyes: Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Skin: Wear appropriate protective gloves to prevent skin exposure.

Clothing: Wear appropriate protective clothing to prevent skin exposure.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Colorless transparent liquid

Physical Constants:**Boiling Point:** 554 °F (290 °C) (760 mm)**Molecular Formula:** C₉H₂₀O₅Si**Formula Weight:** 236.34**Water Solubility:** NA**Density:** 1.070±0.005**Flash Point:** 30.0 °F (110.0 °C) Pensky-Martens Closed Cup**SECTION 10- STABILITY AND REACTIVITY****Chemical Stability:** May decompose on exposure to moist air or water. Reacts with water.**Conditions to Avoid:** Incompatible materials, exposure to moist air or water.**Incompatibilities with Other Materials:** Strong oxidizing agents, strong acids, water, bases, peroxides.**Hazardous Decomposition Products:** Carbon monoxide, carbon dioxide, silicon dioxide, methanol.**Hazardous Polymerization:** Will not occur.**SECTION 11- TOXICOLOGICAL INFORMATION**

Information on toxicological effects

Information on likely routes of exposure

Inhalation: Do not inhale this material.**Skin contact:** Avoid contact with skin.**Eye contact:** Causes serious eye damage.**Ingestion:** Do not ingest.

Symptoms related to the Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and physical, chemical and blurred vision.

Toxicological characteristics: Liquid or vapors can react with moisture in the eye to form methanol, an alcohol which can cause temporary or permanent blindness depending on exposure. Human exposure to methanol may result in illness, systemic poisoning, blindness, optic nerve damage and perhaps death, after being ingested, absorbed through the skin or inhaled. Death due to cardiac or respiratory failure has been reported in some cases from consumption of as little as 30 mls.

Information on toxicological effects

Acute toxicity: Not classified.

Components Species Test Results: Methanol (CAS 67-56-1)

Acute Inhalation: LC50 Rat 22500 ppm, 8 hours**Oral:** LD50 Rat 6200 mg/kg**Skin corrosion/irritation:** Prolonged skin contact may cause temporary irritation. Based on available data, the classification criteria are not met. Serious eye damage.

Respiratory or skin sensitization: Respiratory sensitization Due to lack of data the classification is not possible.

Skin sensitization: Due to lack of data the classification is not possible.

Germ cell mutagenicity: No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity: This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) not listed.

Reproductive toxicity Due to lack of data the classification is not possible.

Specific target organ toxicity -Due to lack of data the classification is not possible.

Repeated exposure: Aspiration hazard Due to lack of data the classification is not possible.**Chronic effects:** May cause damage to organs through prolonged or repeated exposure.**SECTION 12- ECOLOGICAL INFORMATION****Ecotoxicity:** The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability: No data is available on the degradability of this product.

Bio accumulative potential: No data available for this product.

Partition coefficient n-octanol / water (log Kow)

Methanol: (CAS 67-56-1) -0.77

Mobility in soil: No data available.

Other adverse effects: No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13—DISPOSAL CONSIDERATIONS

Product Disposal instructions: Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material and its container must be disposed of as hazardous waste. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazardous waste code: The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused: Dispose of in accordance with local regulations.

Contaminated packaging: Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Contact a licensed professional waste disposal service to dispose of this material. Offer surplus and non-recyclable solutions to a licensed disposal company.

SECTION 14 –TRANSPORT INFORMATION

Proper Shipping Name: None

Hazard Technical Name: None

Hazard Class: N/A

UN/NA Number: None

Packing Group: N/A

SECTION 15– REGULATORY INFORMATION

TSCA: CAS# 2530-83-8 is listed on the TSCA inventory.

Health & Safety Reporting List: None of the chemicals are on the Health & Safety Reporting List.

Chemical Test Rules: None of the chemicals in this product are under a Chemical Test Rule.

Section 12b: None of the chemicals are listed under TSCA Section 12b.

TSCA Significant New Use Rule: None of the chemicals in this material have a SNUR under TSCA.

CERCLA Hazardous Substances and corresponding RQs: None of the chemicals in this material have an RQ.

SARA Section 302 Extremely Hazardous Substances: None of the chemicals in this product have a TPQ.

Section 313 No chemicals are reportable under Section 313.

Clean Air Act:

This material does not contain any hazardous air pollutants.

This material does not contain any Class 1 Ozone depleters.

This material does not contain any Class 2 Ozone depleters.

Clean Water Act:

None of the chemicals in this product are listed as Hazardous Substances under the CWA.

None of the chemicals in this product are listed as Priority Pollutants under the CWA.

None of the chemicals in this product are listed as Toxic Pollutants under the CWA.

OSHA: None of the chemicals in this product are considered highly hazardous by OSHA.

STATE CAS# 2530-83-8 is not present on state lists from CA, PA, MN, MA, FL, or NJ.

California Prop 65: no Significant Risk Level: any of the chemicals in this product are listed.

European/International Regulations

European Labeling in Accordance with EC Directives

Hazard Symbols: Not available.

Risk Phrases: Safety Phrases: S 24/25 Avoid contact with skin and eyes.

SECTION 16 – OTHER INFORMATION

HMIS HAZARD RATINGS 0 = INSIGNIFICANT; 1 = SLIGHT; 2 = MODERATE; 3 = HIGH; 4 = EXTREME

HEALTH: 3 FLAMMABILITY: 1 PHYSICAL HAZARD: 1 REVISION DATE:05/05/2017

The information and recommendations in this publication are, to the best of our knowledge, reliable. Suggestions made concerning uses or applications are only the opinion of Ultra Durable Technologies. Users should make their own tests to determine the suitability of these products for their own particular purposes. However, because of numerous factors affecting results, ULTRA DURABLE TECHNOLOGIES MAKES NO WARRANTIES OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING THOSE OF MERCHANT ABILITY AND FITNESS FOR PURPOSE, other than that the material conforms to its applicable current Standard Specifications. Statements herein, therefore, should not be construed as representations or warranties. The responsibility of Ultra Durable Technologies for claims arising out of reach of warranty, negligence, strict liability, or otherwise is limited to the purchase price of the material. Statements concerning the use of the products of formulations described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is assumed. Standard Specifications, although current at the time of publication, are subject to change without notice. For the latest Standard Specification contact our nearest sales office. Important Notice to Purchaser: Your results may vary due to differences in test types and conditions. You must evaluate and determine whether the product is suitable for your intended application. Ultra Durable Technologies' exclusive warranty is as follows: If Ultra Durable Technologies products are proved defective, the user's exclusive remedy will be, at Ultra Durable Technologies option, to replace the defective product or to refund the purchase price for the defective quantity. Except for the replacement or refund remedies, Ultra Durable Technologies is not liable for direct damages or liable for indirect, incidental or consequential damages, regardless of the legal theory asserted, including negligence and strict liability.